HEXAGON

TubeInspect

Streamline your entire bending operation

TubeInspect is a non-contact optical measurement cell designed for accurate, reliable, and fast inspection of tubes and wires. Built to handle the demands and harsh environments of modern production, it helps you streamline processes for faster throughput.

Reliable accuracy


- Smooth operation in harsh conditions due to automatic temperature compensation
- Reduce downtime risks and ensures smooth operations with the embedded CPU
- User-independent measurements with automatic controls and high-quality glass references
- Each cell passes a DAkkS accredited acceptance test before delivery

Designed for production

- Manual and automated functionality
- Robust construction suitable for shop floor placement
- Automation-ready
- Simple operation requires only 5 minutes training for defined part

Low lifetime costs

- Reduce energy consumption with power-saving LEDs and a standard 100-240V power supply
- Highly stable cell ensures long-term reliability
- Ecofriendly design minimises environmental impact
- No moving parts within the measurement system



Versatile TubeInspect range

- Available in two sizes: M and XL
- Choose standard or high-end resolution (5 or 7 series) for each size
- Built to meet each customer's measurement needs

Quick return on investment (ROI)

- Integrated TubeInspect screen centralises critical information within operators' view for faster workflows
- Gain more production time for benders as TubeInspect adapts to tube changes instantly
- Reduce material waste, and replace all bulky physical gauges, for a streamlined, cost-effective workflow

Countless tube measurement options

- Rotary draw bending parts (LRA)
- Bend-in-bend geometries
- Freeform bent parts
- Formed ends and fittings
- Flexible and long brake lines
- Branched parts
- Rectangular cross-section tubes

Bending machine connection


- Compatible with most worldwide bender makers
- Calculate values for bender correction
- Send data instantly to bending machine
- Minimise number of correction loops – correct all bends in one step

Greater flexibility

- Enable flexible production workflows with CAD
- import of circular and rectangular tubes
- Easy reverse engineering of existing tubes
- Extensive possibilities for transfer of existing tube databases to BendingStudio XT
- Measure complex ends and brackets with CAD ADAPTER

TubeInspect





Specifications


Solution specifications

	35 M	37 M	35 XL	37 XL
Measurement technology	High-resolution camera array			
Measurable tube diameter	2-125 mm	0.8-125 mm	3-200 mm	1.5-200 mm
Measurable diagonal for rectangular tubes	8 -125 mm	2-125 mm	12-200 mm	8-200 mm
Measuring volume	1000 x 580 x 400 mm		2600 x 1250 x 700 mm	
Max. tube length	Unlimited (with repositioning)			
Bending angle	1-340°			
Min. straight between bends	Bend-in-bend and freeform possible			
Measurement accuracy (tube sheath deviation)	0.035 mm (1σ)		0.085 mm (1σ)	
MPE (E) [1]	80 µm + 20 µm * Length [m]		95 µm + 20 µm * Length [m]	
CAD ADAPTER	no	yes	no	yes
Tubes with rectangular cross section	yes			
Automation compatibility	no	yes	no	yes


Hardware specifications

	35 M	37 M	35 XL	37 XL
Measurement speed	> 3 sec/measurement			
Camera array	8 high-resolution digital cameras with GigE technology		16 high-resolution digital cameras with GigE technology	
Resolution	3 MP	12 MP	3 MP	12 MP
Reference field	Three-dimensional glass reference surface			
System dimensions (W x D x H)	1140 x 746 x 1140 mm		2980 x 1640 x 2300 mm	
Weight	260 kg		1250 kg	
Power requirement	100-240 V 50-60 Hz		100-240 V 50-60 Hz	
Max. AC Input	772 VA		1700 VA	
Operation AC [2]	215 VA		690 VA	
Power saving mode	130 VA		265 VA	
Operating temperature	5-45°C			
Relative humidity	10-90% not condensing			
Marks of conformity	CE, UKCA			











[1] MPE (Maximum Permissible Error) – determination of the length measurement error E acc. VDI/VDE 2634 Part 1:2002, calibration certificate according to ISO 17025 accreditation from the German Accreditation Body (DAkkS).

[2] Image acquisition, ground-LED and screen activated.

Hexagon is the global leader in measurement technologies. We provide the confidence that vital industries rely on to build, navigate, and innovate. From microns to Mars, our solutions ensure productivity, quality, safety, and sustainability in everything from manufacturing and construction to mining and autonomous systems.

Hexagon (Nasdaq Stockholm: HEXA B) has approximately 24,800 employees in 50 countries and net sales of approximately 5.4bn EUR.

Learn more at hexagon.com

© 2025 Hexagon AB and/or its subsidiaries and affiliates. All rights reserved.